

Tube Dimention		15''AES
Electrical	unit	
Heater current at 6.3V	mA	300
Focus Lens		QPF
Deflection angle(approximate)		
Diagonal (degree)	(---)°	90
Horizontal (degree)	(---)°	78
Vertical (degree)	(---)°	60
Optical		
Neck Demention(f)	mm	29.1
Center Transmission rate	%	57
Mechanical		
Overall Length	mm	350.2±6.5
Neck Length	mm	147.2±3.0
Minimum useful screen(Projected)		
Diagonal	mm	356.0
Horizontal	mm	285.5
Vertical	mm	214.0
Weigth	kg	8.0
Dimensional outlines		
Z Point toLug-Typical 1	mm	34.0
Z Point toLug-Typical 2	mm	

Tube Dimention		15''AES
Maximum/Minimum Design Rating		
Anode	kV	27.5/20
Total anode current	mA	450
G3(Focusing electrode) voltage	kV	10
Heater voltage (AC or DC)	V	6.3
Others		
RCOEK		1.15
Dot pitch	mm	0.28
DY Impedance(54K)		
Lh	mH	0.299
Lv	mH	5.920
Rh	ohm	0.534
Rv	ohm	9.500
DY Impedance(69K)		
Lh	mH	0.180
Lv	mH	5.800
Rh	ohm	0.345
Rv	ohm	9.500