

Tube Dimention		17"FS
Electrical	unit	
Heater current at 6.3V	mA	300
Focus Lens		QPF
Deflection angle(approximate)		
Diagonal (degree)	(---)°	90
Horizontal (degree)	(---)°	78
Vertical (degree)	(---)°	60
Optical		
Neck Demention(f)	mm	29.1
Center Transmission rate	%	53
Mechanical		
Overall Length	mm	382.1±6.5
Neck Length	mm	151.8±3.0
Minimum useful screen(Projected)		
Diagonal	mm	407.1
Horizontal	mm	327.5
Vertical	mm	246.2
Weigth	kg	8.9
Dimensional outlines		
Z Point toLug-Typical 1	mm	20.0
Z Point toLug-Typical 2	mm	

Tube Dimention		17"FS
Maximum/Minimum Design Rating		
Anode	kV	29/20
Total anode current	mA	700
G3(Focusing electrode) voltage	kV	10
Heater voltage (AC or DC)	V	6.3
Others		
RCOEK		1.15
Dot pitch	mm	0.28
DY Impedance(69K)		
Lh	mH	0.183
Lv	mH	4.300
Rh	ohm	0.447
Rv	ohm	6.961
DY Impedance(82K)		
Lh	mH	/
Lv	mH	/
Rh	ohm	/
Rv	ohm	/